

Høllin – technical info

Standard equipment

- Wi-fi
- Computer for presentations
- Teleprompter
- Cinema canvas 12m x 5m
- Projector:
 - Epson EB-Z8455WU
 - 7000 Ansi Lumens
 - Resolution: 1920x1200 dots (HD)
- Wireless microphones
- Head-set
- Stage:
 - length 17,8m
 - depth from back wall to seats: 10m
 - stage depth: 7m

Lights

- Console:
 - Jands Vista 5
 - GrandMA Ultralight
- Lamps:
 - S4 750w 25°-50° & 15°-30°/
 - ADB Fresnell 1kW & 2kW/
 - PAR 64 /
 - LED ColourForce72
 - Martin Mac 250 & 700

Sound

- PA
 - L-acoustics, kilo/kiwa. Hi-Q monitors, SB 118 sub, 112P mon og 108P mon
- FOH console
 - Soundcraft Vi3000 + 64/32 digital stagebox
- Monitor console
 - Yamaha M7CL 48

Cinema equipment

- Projector: Barco PD2K-19B
- Server: Doremi ShowVault 3TB Digital Cinema
- Sound: Dolby CP750 Digital Sound Processor, 5.1 format usual
- Main format: DCP
- Myndastødd: 10-11m breitt og uml. 5,6m høgt
- The projector can also play Blu-ray & DVD

Interpreter equipment

- The interpreter equipment is branded DIS

- 2 boxes with a interpreter panel each. One language can be interpreted at a time in each box. The boxes can be set up in any room except Eystur- & Vesturstova.
- 25 table panels/microphones. 2 people can sit at each panel and have a headset each.
- 50 receivers/hearsets for audiences. Each with 4 channels.